

40 zone hybrid control panel

The i-on40H is a highly versatile control panel. With 40 zones out of the box it is expandable up to 80 hybrid zones. It is suitable for larger floor plans and properties with outbuildings and is compatible with Eaton's full range of wired and radio peripherals and plug on communicators.



Built with cyber security in its DNA, the i-on40H is Eaton SecureConnect™ Cloud and App enabled.

Multiple communication options

Built-in Ethernet port and optional PSTN or GSM allows you to tailor installations to the properties needs.

Eaton SecureConnect™ Cloud and App

Control and monitor your panel through the cloud anytime anywhere. Provide your customers with peace of mind with a secure App for convenient control of their system.

Simple visual verification

Connect Eaton security cameras to the i-on40H panel for an additional layer of security. Capture images locally on an SD card and view through App or email.

At a glance...

- 30 radio and 10 wired zones expandable to 80
- Hybrid expansion using EXP-R10/R30/W10/PSU
- Ethernet / web server / virtual keypad
- Visual verification
- Perimeter zone functionality
- Plug on ARC/Speech/SMS for PSTN/GSM
- Class leading Scantronic radio
- Email notifications
- EN50131 Grade 2: Independently approved




Powering Business Worldwide

Scantronic product data sheet

Product specification

| | |
|-----------------------|--|
| Product Code | i-on40H-KPZ (Supplied with KEY-KPZ01) |
| Compliance | EN50131-1:2006 + A1:2009 Grade 2 and environmental class II, EN50131-3:2009, EN50131-6:2008, BS8243:2010, PD6662:2017 |
| Zones on board | 30 Radio and 10 wired on board, expandable to 80, all fully programmable |
| Total number of buses | One which accepts up to 20 bus devices (keypads, expanders and power supplies) |
| Number of users | 50 user codes, 4 digit PIN number, proximity, remote control or radio panic button |
| Number of outputs | Two programmable relay outputs. Two 500mA open collector programmable outputs. 12 low-current outputs for plug-by communicators and 10 radio outputs |
| Visual Verification | Up to 4 IP cameras |
| Power supply | Conforms to EN50131-6:2008 Type A power supply, rated power output 1.0A. 650mA is available for auxiliary power |
| Battery | Accepts a 12v standby battery up to 7Ah rechargeable lead acid, gel type |
| Temperature range | Environmental class II. Tested -10°C to 55°C @ 93% RH |
| Weight | 2.2kg |
| Dimensions | 384 x 245 x 94mm |



Compare product compatibility with our easy to read chart: www.eaton.com/security-works-with

Eaton
Electrical Sector
EMEA Route de la Longeraie 7
1110 Morges, Switzerland

Eaton Electrical Products Ltd
Security House,
Vantage Point Business Village,
Mitcheldean, Gloucestershire
GL17 0SX

Tel: +44 (0)1594 545 400
Email: securitysales@eaton.com
Web: www.myscantronic.com

Eaton is a registered trademark of Eaton Corporation.

All other trademarks are property of their respective owners.