

**DEL**TABELL E

Low power external sounder with strobe

**DEL**TABELL PLUS

Low power external sounder with strobe and back-light



## ***AROUND THE CLOCK VISUAL DETERRENT TO MAXIMISE YOUR SECURITY***

The Deltabell E and Plus are the latest external sounders from Pyronix. Both sounders feature engineer friendly features such as the unique levelling mechanism and modular components that make simple sounder installations a reality.

Both external sounders incorporate the same features that are described overleaf. However, the Deltabell Plus has a fully back-light option, which enables around the clock visual deterrent to maximise your security.

The Deltabell E and Plus are available in a variety of different colours:



**Available Base Colours:** Red, Green, White, Amber, Blue and Black

**Available Lid Colours:** Red, White, Yellow, Black\*, Blue\* and Chrome\*

\*Not recommended for Deltabell Plus



# FEATURES

## Security and peace of mind.

The Deltabell has front and rear tamper protection and in the event of a potential sabotage attack, the 109bBA sounder provides a distinctive audible warning. In addition, the comfort LEDs can be disabled so that potential intruders are not aware of the power status.

The electronic elements on the printed circuit board are protected by a fully sealed unit with a rubber gasket providing added protection in harsh environments and giving your customer peace of mind that the Deltabell will always sound in the event of an alarm activation.

**109 dBA sounder.** Piezo sounder with high decibel output.



## Engineer hold-off facility.

The Deltabell engineer hold-off facility means that when initially powered with the tamper switch open, the sounder will not activate.

## Remote engineer hold-off facility.

There is also the capability for remote engineer hold-off which is invaluable when you are servicing the system enabling easy maintenance. It can be turned on at any time by applying 0V to this dedicated terminal which will then disable the tamper.

## LED enable/disable.

The comfort LEDs on the Deltabell can be disabled so potential intruders are not aware of the power status.



## Unique levelling mechanism.

A spirit level is supplied so that you can easily mount the Deltabell. In addition, to make the installation as simple as possible, revolving guide holes are used to save time lining up screw and drill holes.



**SCB/SAB Mode:** Self Contained Bell or Self Activating Bell mode.

**Hinged cover.** The Deltabell has a hinged cover that locks into place so that both your hands are free to work on the sounder.



**Fully back-lit cover.** The Deltabell low power modular unit back-lights the cover (Deltabell Plus only)



## Electrical specification.

### Operating Voltage

Supply:	9-16 V DC (13.5 nominal)
Protected:	Reverse polarity protected

### Current Consumption

Quiescent Current:	< 60 mA
Alarm Current:	< 300 mA

### Strobe

Strobe Duration:	100 ms
Strobe Frequency:	1Hz

## Dimensions.

[W]	290 mm
[H]	285 mm
[D]	50 mm



## Packing information.

**Minimum quantity:** 10  
**Minimum order for screen print:** 40  
**Warranty:** 2 years  
**Designed:** UK

**Dummy bases also available**

**UK design trade mark.**

Application number 4009274

## Compliance.

Europe. **CE**  
 Suitable for use in  
 EN50131-1 systems  
 Security grade **3**,   
 Environmental class **3**