


SFX/C5-FTP-PVC-GRY

Category 5e, 4pr FTP Grey PVC (100MHz)



Cable Construction

Conductor	Bare Copper
Conductor Diameter (mm)	0.50 ±0.02
AWG	24

Insulation	HDPE
Insulation Thickness (mm)	0.18
Insulation Diameter (mm)	0.88 ±0.08
Insulation Colours	Blue/White/Blue;Orange/White/Orange;Green/White/Green;Brown/White/Brown

Clear Polyester Tape	>=115%
----------------------	--------

Drain Wire

Conductor	Tinned Copper
Conductor Diameter (mm)	0.40 ±0.01

Al-PET Shield	>=115%
---------------	--------

Nylon Rip-Cord	White 210D
----------------	------------

Jacket	PVC
--------	-----

Jacket Thickness (mm)	0.55 ±0.05
-----------------------	------------

Overall Diameter (mm)	6.10 ±0.30
-----------------------	------------

Jacket Colour	Grey RAL 7004
---------------	---------------

Sheath Printing	Cat 5e FTP 4 PR 24AWG PVC ISO/IEC 11801 ANSI/TIA 568C.2 (PO) (m)
-----------------	--

Reaction to Fire	Eca
------------------	-----

Electrical Characteristics

Max Conductor DC resistance @ 20°C	<95Ω/km
------------------------------------	---------

Rated Temperature	80°C
-------------------	------

Impedance (1-100MHz)	100Ω ±15Ω
----------------------	-----------

Test Standards	ISO/IEC 11801; ANSI/TIA 568-C.2
----------------	---------------------------------

