TECHNICAL DATASHEET

ECO DOOR HOLDERS



Arguably the single most important fire safety mechanism - electromagnetic door holders guard against the lethal spread of toxic smoke and fumes - by far the greatest cause of death in fires.

The Vimpex EN 1155 approved Eco range of door holders offers the installer a choice of holding power and installation accessories.

Mounted onto a fixed surface, these door holders ensure retention of the fire door by means of a smart metallic keeper plate. Interfaced with the fire alarm system, the door holders are de-energised as soon as the fire is detected thus releasing the door without the potentially harmful delay suffered by other types of devices.



FEATURES

- · Two holding forces available 200N and 500N
- · Zero residual force
- Available in 230 V ac and 24 V dc
- · High quality and cost effective
- · Approved to EN 1155 and CE Marked

PART NUMBERS - SPARES & ACCESSORIES

DH/KP/Standard: Standard Swivel Keeper Plate
 DH/FB: Floor Mounting Bracket
 DH/KP/LP/500: Low Profile Keeper Plate

• DH/CHO: Keeper Plate with Extension Chain and Rubber Ring

SPECIFICATION

Part Number:	Description	Rated Voltage	Nominal Current	Holding Force	Temperature Range	IP Rating	Power Closure Power Size	Weight
DH/EC/24/200:	Surface DC	24 V dc	50 mA	200 N	0 to 40°C	IP 51	3 to 6	360g
DH/EC/24/500:	Surface DC	24 V dc	50 mA	200 N	0 to 40°C	IP 51	3 to 6	500g
DH/EC/230/200:	Surface AC	230 V ac	5 mA	200 N	0 to 40°C	IP 51	3 to 6	360g

INSTALLATION

Door Holder










Dimensions (mm)
Keeper Plate

4 CSK HOLES Dia. 5



DS/ECODH-TD/ISS 2

We reserve the right to change or amend any design or specification in line with our policy of continuing development and improvement.

Vimpex LTD

Star Lane, Great Wakering, Essex SS3 OPJ, UK

- t. +44 (0) 1702 216999
- e. sales@vimpex.co.uk www.vimpex.co.uk

Vimpex Interguard AB

- t. +46 (0) 36 37 10 65
- e. sales@vimpex.se



